

## Liquiphant FTL62 - the coated sensor for aggressive media

### A level switch for aggressive and pumpable liquids



Więcej informacji i aktualne ceny:

[www.pl.endress.com/FTL62](http://www.pl.endress.com/FTL62)

#### Korzyści:

- Universal measuring principle for limit detection – proven vibronic technology
- Developed according IEC 61508 for highest safety – SIL2/3 applications (3rd party approved)
- Periodic proof testing is quickly and simple organized with guided wizards via the SmartBlue-App or via a test button or magnetic pin from outside. Via these ways, you can initiate the instrument for a fast and easy testing of the safety loop
- Heartbeat Technology allows safe, continuous diagnostics and a simple verification
- **Heartbeat Diagnostics:** Permanent diagnostics increase the safety of the plant. You connect your device via the SmartBlue-App and you easily have real time diagnostics at hand
- **Heartbeat Verification:** The device can be verified without process interruption. The verification report is generated automatically
- **Heartbeat Monitoring:** With the frequency tracking of the sensor data you have all information at hand for predictive maintenance and process optimization strategies

#### Kluczowe parametry

- **Temperatura procesu** Temperatura procesu
- **Absolutne ciśnienie medium / Wartość graniczna nadciśnienia**  
Vacuum...40 bar Vacuum...580 psi
- **Min. gęstość medium** Min. gęstość medium

**Zastosowanie:** Liquiphant FTL62 has a strong focus on specific applications with aggressive liquids and simplicity with easy proof testing, reliability and safety (SIL) with compliance to IEC 61508, API 2350 and

WHG. The vibronic device is determined for a safe and active measuring technology in aggressive liquids and want a reliable and proven point level detection for tank overfill prevention and pump dry run protection. The FTL62 is easy to use, has a digital connection and gives a real-time data at hand.

## Funkcje i specyfikacja

### Sygnalizacja poziomu / Ciecze

#### Zasada pomiaru

Vibration Liquids

#### Charakterystyka / Aplikacja

Compact vibronic device with highly corrosion-resistant coating for aggressive media,

Optional extension tube up to 3 m (9.8ft),

Modular housing concept

#### Wersje specjalne

Wersje specjalne

#### Zasilanie / Komunikacja

19...253V AC / 2-wire,

10...55V / DC-PNP 3-wire,

9...20V DC with relay DPDT,

19...253V AC or 19...55V DC with relay DPDT,

2-wire NAMUR,

2-wire PFM

## Sygnalizacja poziomu / Ciecze

**Temperatura otoczenia**

-60 °C...+70 °C

(-51 °F...+158 °F)

**Temperatura procesu**

Temperatura procesu

**Absolutne ciśnienie medium / Wartość graniczna nadciśnienia**

Vacuum...40 bar

Vacuum...580 psi

**Min. gęstość medium**

Min. gęstość medium

**Główne części wchodzące w kontakt z medium**

ECTFE,

PFA (Edlon, RubyRed or conductive)

316L

Enamel

**Przyłącze technologiczne**

Przyłącze technologiczne

**Długość czujnika**

Up to 3 m (9.8ft)

---

**Sygnalizacja poziomu / Ciecze****Wyjście**

2-wire direct load

DC-PNP 3-wire

Relays

NAMUR

PFM

Bluetooth® wireless technology

---

**Certyfikaty / Dopuszczenia**

ATEX, IEC Ex

---

**Safety approvals**

Safety approvals

---

**Design approvals**

EN 10204-3.1

ASME B31.3 Process Piping

CRN

---

**Opcje**

Ambient temperature down to -60 °C (-76 °F),

Heavy duty stainless steel housing

---

**Elementy składowe**

FTL325P Interface PFM

FTL325N Interface NAMUR

Więcej informacji [www.pl.endress.com/FTL62](http://www.pl.endress.com/FTL62)